

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/24192174>

# Occupational exposure to diesel engine exhaust: A literature review

Article in *Journal of Exposure Science and Environmental Epidemiology* · March 2009

DOI: 10.1038/jes.2009.21 · Source: PubMed

---

CITATIONS

93

---

READS

223

3 authors, including:



Anjoeka Pronk

TNO

63 PUBLICATIONS 758 CITATIONS

[SEE PROFILE](#)



Joseph Coble

United States Department of Labor

70 PUBLICATIONS 2,418 CITATIONS

[SEE PROFILE](#)

Some of the authors of this publication are also working on these related projects:



Agricultural Health Study [View project](#)



Published in final edited form as:

*J Expo Sci Environ Epidemiol*. 2009 July ; 19(5): 443–457. doi:10.1038/jes.2009.21.

## Occupational exposure to diesel engine exhaust: A literature review

Anjoeka Pronk<sup>a</sup>, Joseph Coble<sup>a</sup>, and Patricia Stewart<sup>b</sup>

<sup>a</sup> Division of Cancer Epidemiology and Genetics, National Cancer Institute, Rockville, MD, USA

<sup>b</sup> Stewart Exposure Assessments, LLC, Arlington, VA, USA

### Abstract

**Background**—Diesel exhaust (DE) is classified as a probable human carcinogen. Aims were to describe the major occupational uses of diesel engines and give an overview of personal DE exposure levels and determinants of exposure as reported in the published literature.

**Methods**—Measurements representative of personal DE exposure were abstracted from the literature for the following agents: elemental carbon (EC), particulate matter (PM), carbon monoxide (CO), nitrogen oxide (NO), and nitrogen dioxide (NO<sub>2</sub>). Information on determinants of exposure was abstracted.

**Results**—In total, 3528 EC, 4166 PM, 581 CO, 322 NO, and 1404 NO<sub>2</sub> measurements were abstracted. From the 10,001 measurements, 32% represented exposure from on-road vehicles, and 68% from off-road vehicles (30% mining, 15% railroad, and 22% other). Highest levels were reported for enclosed underground work sites where heavy equipment is used: mining, mine maintenance, and construction, (EC: 27-658 µg/m<sup>3</sup>). Intermediate exposure levels were generally reported for above ground (semi-)enclosed areas where smaller equipment was run: mechanics in a shop, emergency workers in fire stations, distribution workers at a dock, and workers loading/unloading inside a ferry (generally: EC < 50 µg/m<sup>3</sup>). Lowest levels were reported for enclosed areas separated from the source such as drivers and train crew, or outside such as surface mining, parking attendants, vehicle testers, utility service workers, surface construction and airline ground personnel (EC < 25 µg/m<sup>3</sup>). The other agents showed a similar pattern. Determinants of exposure reported for enclosed situations were ventilation and exhaust after treatment devices.

**Conclusions**—Reported DE exposure levels were highest for underground mining and construction, intermediate for working in above ground (semi-)enclosed areas and lowest for working outside or separated from the source. The presented data can be used as a basis for assessing occupational exposure in population-based epidemiological studies and guide future exposure assessment efforts for industrial hygiene and epidemiological studies.

### Keywords

diesel exhaust; occupational; review; exposure; determinant

### Introduction

Diesel engines have a wide range of industrial applications, including on and off-road equipment used, for example, in the mining, railroad, construction, and transportation

industries. The use and application of diesel engines in industrial processes became widespread between the 1930s and 1950s (HEI, 2002). The National Institute of Occupational Safety and Health (NIOSH) estimated that approximately 1.4 million workers in the United States (US) were occupationally exposed to diesel exhaust (DE) between 1981 and 1983 (NIOSH, 1983). A second study estimated that 3 million workers were exposed to DE in the 15 countries of the European Union between 1990–1993 (Kauppinen, et al., 2000).

DE contains a complex mixture of gases and particulates. Gaseous constituents include oxides of carbon, nitrogen, and sulfur, and low molecular weight hydrocarbons (Ris, 2007). The particulate fraction is primarily in the submicron range and consists of an insoluble elemental carbon (EC) core and an adsorbed surface coating of relatively soluble organic carbon (OC). EC and OC typically constitute 33–90% and 7–49%, respectively, of the particulate mass (EPA, 2002). The assessment and characterization of DE is complicated because its chemical composition is affected by changes in engine technology and fuel composition over time (EPA, 2002).

Health effects of DE exposure include eye, throat and bronchial irritation, cough, phlegm, and neurophysiological symptoms (Lloyd, et al., 2001; Ris, 2007). In addition, DE is considered a probable human carcinogen by the International Agency for Research on Cancer (IARC) (1989). A general limitation of the almost 50 epidemiological studies investigating cancer in workers exposed to DE is the lack of quantitative data on historical exposure (Rogers, et al., 2005; Silverman, 1998).

This paper describes the major occupational uses of diesel engines and gives an overview of personal exposure levels to diesel exhaust and determinants of exposure as reported in the published literature. The data were developed as a basis for assessing occupational exposure to DE in population-based epidemiological studies. In addition, the data can guide future exposure assessment efforts for industrial hygiene and epidemiological studies.

## Methods

Literature on occupational DE exposure was identified from MEDLINE, TOXLINE, NIOSHTIC, and the NIOSH Health Hazard Evaluation database using the search terms 'diesel', 'diesel particulate matter', 'diesel exhaust', 'occupational', and 'exposure'. In addition, personal archives added literature not present in these databases. Literature from 1957 through 2007 was identified. Information on occupational DE exposure was abstracted. The information presented includes a brief description of the industry and processes and an overview of exposure measurements and reported determinants. The information is organized by on-road and off-road equipment. Off-road uses were further categorized into mining, railroad, and other applications.

The assessment of exposure to DE is complicated because no single constituent of DE is considered a unique marker of exposure (Lloyd, et al., 2001). In the past, investigators have used several non-specific components of DE as surrogates, such as respirable particulate matter ( $PM_R$ ), carbon monoxide (CO), nitrogen oxide (NO), or nitrogen dioxide ( $NO_2$ ). In the 1990s, two more specific surrogates for DE have been increasingly used: EC and submicron particulate matter ( $PM_S$ ) (Steenland, et al., 1998). To evaluate both current and past exposure levels, EC,  $PM_R$  (including  $PM_{2.5}$ ),  $PM_S$ ,  $NO_2$ , NO, and CO were selected for this report. For these agents, all occupational personal measurement data reported in the literature were summarized in a database. Area samples that were likely representative of personal exposures were also included. Because most of the agents are not specific for diesel exhaust, an indication of the presence of diesel engines was required for inclusion. For

practical reasons, only agents with a total of 5 or more measurements on all jobs combined in a study were included. Studies that did not report sample size were included when it could be inferred from the text that at least 5 measurements were likely for an agent. Efforts were made to exclude studies reporting the same exposure data.

The abstracted information on the measurements included industry, description of job/task/location, country, sample year (when not provided publication year was used), type of sample (area or personal), number of samples, sampling duration, sampling and analytic method, and summary statistics. All sampling durations except peak measurements were included and were categorized as <1 hour, 1–4 hours, or ≥4 hours. The arithmetic mean (AM) and standard deviation (SD) and geometric mean (GM) and geometric standard deviation (GSD) were included. Summary statistics were calculated when only individual measurement results were presented. When averages for similar jobs were presented in a single publication, these were combined into broader job categories by weighting the AMs and GMs by the number of measurements. For calculations, non-detectable (ND) values or averages were substituted by the detection limit divided by  $\sqrt{2}$  (Hornung, et al., 1990). When means were presented without specifying the number of measurements, an unweighted average was calculated. In addition, the range of SDs or GSDs across jobs is presented. When the AM was not reported, it was estimated. When the GM and GSD were reported, a lognormal distribution was assumed and the AM was estimated using the formula (Aitchison, et al., 1969):

$$AM = GM \times \exp[1/2 \times (\ln(GSD))^2]$$

If only the range was provided, the GM was estimated by squaring the midpoint of the log transformed minimum and maximum levels and the GSD was estimated by squaring the range of the log transformed values divided by four (Hein, et al., 2008). The units of EC and PM are in  $\mu\text{g}/\text{m}^3$ , and CO, NO and NO<sub>2</sub> units are in ppm. When units of the gases were in  $\text{mass}/\text{m}^3$ , they were converted to ppm assuming standard room temperature and pressure.

Determinants of exposure are described that were either explicitly identified or implicitly identified by contrasting scenarios. Explicitly identified determinants for area measurements not representative of personal exposure, and measurements of other DE surrogates not selected for the measurement summary herein are also presented. When provided by the original paper, the exposure levels for the contrasting scenarios are given in the text. Statistical significance is indicated when reported by the original study investigators.

## Results

Almost 300 papers and reports were reviewed. Fifty-seven studies reported on personal or representative area exposure measurements that did not overlap. Of these studies, 28% included samples taken after 2000 (5026 samples), 53% in the 1990s (3003 samples), 12% in the 1980s (1569 samples), and 7% in the 1970s (403 samples). In total, 10,001 samples were reported, of which 32% represented exposure from on-road vehicles. The remaining 68% was taken in the mining industry (30%), the railroad industry (15%), and other off-road operations (22%). Seventy-four percent of the samples were taken in the US. The rest were taken in Australia, Canada, Georgia and several European countries. The 10,001 samples consisted of EC measurements (35%), PM (42%, of which 8% were submicron and 34% were respirable), CO (6%), NO (3%), and NO<sub>2</sub> (14%).

EC was sampled by size selective sampling (submicron, respiratory or inhalable). Analysis was mostly performed by thermo-optical analysis as described in NIOSH method 5040

(Bakke, et al., 2001; Boffetta, et al., 2002; Burgess, et al., 2007; Cohen, et al., 2002; Davis, et al., 2007; Echt, et al., 1995; Garshick, et al., 2002; Liukonen, et al., 2002; McDonald, et al., 2002; NIOSH, 1993; NIOSH, 1998; NIOSH, 1998; NIOSH, 1998; NIOSH, 2006; Ramachandran, et al., 2005; Roegner, et al., 2002; Seshagiri, 2003; Stanevich, et al., 1997; Verma, et al., 2003; Wheatley, et al., 2004; Whittaker, et al., 1999; Woskie, et al., 2002; Zaebst, et al., 1991), but an alternative thermal technique based on coulometric detection was used by some studies (Adelroth, et al., 2006; Groves, et al., 2000; Leeming, et al., 2004; Lewne, et al., 2007). PM was assessed by size selective sampling (submicron or respiratory) and gravimetric analysis in all studies. CO was assessed by direct reading instruments (Hobbs, et al., 1977; NIOSH, 1994; NIOSH, 2005; NIOSH, 2006; Ulfvarson, et al., 1991; Whittaker, et al., 1999) or detector tubes (passive or active) (Bakke, et al., 2001; NIOSH, 1991; Seshagiri, 2003). NO and NO<sub>2</sub> were assessed mostly by passive diffusion sampling tubes (e.g. Palmes or Draeger) (Adelroth, et al., 2006; Ames, et al., 1982; Bakke, et al., 2001; Gamble, et al., 1978; Gamble, et al., 1987; Lewne, et al., 2006; Lewne, et al., 2007; NIOSH, 1986; NIOSH, 1991; NIOSH, 1991; NIOSH, 1991; NIOSH, 1992; NIOSH, 1993; Reger, et al., 1982), but also by direct reading instruments (Hobbs, et al., 1977; Ulfvarson, et al., 1991; Wheeler, et al., 1980; Whittaker, et al., 1999), and NIOSH method 6014 (NIOSH, 2005; Seshagiri, 2003; Verma, et al., 1999). Methods for EC, CO, and NO/NO<sub>2</sub> were not indicated or unclear in 3 studies ((NIOSH, 1986; Zaebst, et al., 1992), (Attfield, 1978) and (Zaebst, et al., 1992), respectively).

An evaluation of emission standards and environmental and occupational regulations regarding exposure to diesel particulate matter and exhaust gases is beyond the scope of this review. A comprehensive review of worldwide standards is summarized by an internet information service on diesel engine emissions (DieselNet).

### On-road vehicles

Currently, almost all heavy duty trucks and buses, and an increasing fraction of medium duty trucks in the US use diesel engines (EPA, 2002). Heavy duty trucks first switched to diesel engines in the 1950s (Steenland, et al., 1990) and sales became predominantly diesel powered in the 1960s and 1970s (EPA, 2002). In the 1990s, the majority of medium duty truck sales and about 30% of light duty truck sales were diesel (EPA, 2002). The switch to diesel engines occurred earlier for large companies than for independent drivers or non-trucking companies (Steenland, et al., 1990). In the US, very few passenger cars or taxis are diesel-fueled, in contrast to about one third of the new passenger cars sales in Europe (Lloyd, et al., 2001).

EC exposure levels for truck, bus, and taxi drivers were generally 1–10  $\mu\text{g}/\text{m}^3$  (Table 1). Reported EC means were generally higher (20–40  $\mu\text{g}/\text{m}^3$ ) for mechanics in truck terminals, bus garages and stand alone maintenance shops (Table 1). EC levels reported for fire fighters were mostly non-detectable, but one study reported an AM of 40  $\mu\text{g}/\text{m}^3$  (Table 1). For other workers, including bus service workers involved in parking, cleaning and refueling, workers at a vehicle testing station, and parking attendants inside a booth, mean exposure levels of  $\leq 11 \mu\text{g}/\text{m}^3$  were reported. The other agents were measured less frequently, but showed a similar exposure pattern (Table 1).

Two large industrial hygiene surveys in the trucking industry reported significantly higher levels of EC and PM<sub>R</sub> in trucks when windows were open vs closed (1.5 vs 1.3 and 19.9 vs 18.5  $\mu\text{g}/\text{m}^3$ , respectively) (Davis, et al., 2007; Zaebst, et al., 1991) and during warm weather vs cold (7.0 vs 2.0  $\mu\text{g}/\text{m}^3$ ) (Zaebst, et al., 1991). A smaller study reported approximately 2-fold higher levels of EC and PM<sub>2.5</sub> for local drivers who worked during the day in a large city compared to long haul drivers driving in the evening on suburban and rural highways (AM: 6.7 vs 4.5 and 128.7 vs 56.0  $\mu\text{g}/\text{m}^3$ , respectively) (Table 1) (Garshick, et al., 2002). A

Swedish study also reported significantly higher NO<sub>2</sub> levels for both bus and truck drivers in the city than in a suburban area (0.04 vs 0.03 and 0.04 vs 0.03 ppm, respectively) (Lewne, et al., 2006). In this study, drivers of diesel and petrol powered taxis had similar exposure levels that were significantly lower than bus and truck drivers' exposure levels (0.025–0.027 vs 0.032–0.036 ppm) (Table 1) (Lewne, et al., 2006). This difference was explained by the long waiting periods taxis spent outside traffic intensive areas. Two large studies using identical sampling protocols and analytical methods showed that EC levels for truck drivers in 2001–2005 (Davis, et al., 2007) were about three times lower than in the 1980s (Zaebst, et al., 1991) (Table 1). In addition, the former of these studies reported a significantly positive correlation between EC level and truck age, which was attributed to higher seepage of DE into older truck cabs due to leaks from the cab's rubber seals (Davis, et al., 2007).

Colder weather compared to warmer weather resulted in higher personal EC exposure levels for mechanics (28 vs 4.8 µg/m<sup>3</sup>) (Zaebst, et al., 1991) and statistically significantly higher area EC levels in a bus depot and truck repair shop (19–36 vs 5–6 µg/m<sup>3</sup>) (Sauvain, et al., 2003), both of which were attributed to decreased ventilation. A study modeling exposure in trucking terminals showed that ventilation, terminal size, the number of workers, and general background levels were significant determinants of EC levels in work area air concentrations, and work location (shop higher than dock) was a significant determinant of both area and personal EC levels (levels not provided in the original article) (Davis, et al., 2006). Two studies, performed in the same bus garages in 1956 and 1979 in the U.K., using the same procedures, showed little difference between area levels of smoke from diesel buses entering and leaving the garage (Commins, et al., 1957; Waller, et al., 1985).

A study of three fire stations reported an observable trend in personal total PM exposure of workers inside two fire stations with closed windows with the number of times a truck made a run. This trend was not observed in a third fire station where windows were open (Froines, et al., 1987). Another study of fire fighters' exposure reported a reduction of EC levels by 76–91% after installation of ceramic filters on the tail pipes of fire engines (Roegner, et al., 2002).

### Off-road applications

Off-road applications include the use of diesel powered heavy equipment, locomotives, fork-lift trucks, ships, tractors, and generators in the mining, railroad, construction, distribution, farming, and the military. The use of off-road diesel engines became widespread between the 1930s and 1950s (HEI, 2002). Off-road vehicle turnover is low and older engines are generally used longer in off-road than in on-road vehicles. In addition, in the US emission standards for non-road equipment are less stringent (DieselNet).

### Mining

Mining operations can be either surface or underground. In surface mining, large excavating equipment is used to remove rock covering the mineral deposit. In underground mines, the mineral deposit is extracted through tunnels and shafts. Diesel powered vehicles may include vehicles for transportation of personnel, haulage trucks, load and dump vehicles, drills, graders, and utility trucks. Mining operations can be classified into coal and metal/nonmetal mines. In the US, diesel engines were first introduced in metal and nonmetal mines in 1939 and in coal mines in 1946 (MSHA, 1998). In the 1970s, the use of diesel engines greatly increased (Haney, et al., 1997; Lachtman, 1983). In 1998, the Mine Safety and Health Administration (MSHA) estimated that 18% of the 971 underground coal mines and 78% of the 261 underground metal/nonmetal mines in the US used diesel engines. Several states in the US ban, or significantly restrict, the use of diesel-powered equipment in underground coal mines. All 1673 surface coal mines and 10474 surface metal/nonmetal

mines were estimated by MSHA to use diesel engines in 1998 (MSHA, 1998). In Europe, diesel engines were introduced for haulage in the 1920s and were extensively used by 1936 in both coal and non-coal mines (MSHA, 1998).

Of the 18 studies reporting exposure measurements, seven were performed in nonmetal mines, three in metal mines, seven in coal mines, and three studies did not specify the mine type (Table 2). For EC, PM<sub>R</sub> and NO<sub>2</sub>, mine types could be compared for a similar time period. No obvious differences in reported levels were observed.

Most studies focused on underground production workers who drilled and blasted at the mine face, loaded and scooped the ore and debris, and hauled the ore and debris to transportation equipment or conveyor belts that further transported it to surface processing areas. Maintenance workers included workers in underground repair shops, warehouse workers, and workers doing infrastructure maintenance located in haulage and travel ways. A comparison between the job categories was possible only for EC and PM<sub>R</sub>. Reported EC levels were highest for underground production workers (AM: 148–658  $\mu\text{g}/\text{m}^3$ ) and lower for underground maintenance workers (AM: 53–144  $\mu\text{g}/\text{m}^3$ ) and underground unspecified and surface workers (AM: 13–66  $\mu\text{g}/\text{m}^3$ ) (Table 2). Highest levels for PM<sub>R</sub> also were reported for underground mining and underground unspecified (AM: 710 – 3637  $\mu\text{g}/\text{m}^3$ ) and lowest for underground maintenance and surface (AM: 556–881  $\mu\text{g}/\text{m}^3$ ). A study reporting on specific jobs within underground mining found average EC exposure levels of 345  $\mu\text{g}/\text{m}^3$  for ram car operators, 222  $\mu\text{g}/\text{m}^3$  for the belt crew, 225  $\mu\text{g}/\text{m}^3$  for continuous miners, 162  $\mu\text{g}/\text{m}^3$  for foremen, and 193  $\mu\text{g}/\text{m}^3$  for miners (Stanevich, et al., 1997). Another study reported that exposure levels to PM<sub>R</sub> were similar for mining personnel (90–460  $\mu\text{g}/\text{m}^3$ ) and supervisors (130–480  $\mu\text{g}/\text{m}^3$ ) (Ambs, et al.).

The use of disposable DE filters was reported to decrease average area PM<sub>5</sub> concentrations at a shuttle car in a coal mine from 1186 to 247  $\mu\text{g}/\text{m}^3$  (Ambs, et al.). In another coal mine, both reusable wire mesh filters and disposable paper filters resulted in lower ram car area PM<sub>5</sub> levels than without filters (AM: 1200 vs 2060  $\mu\text{g}/\text{m}^3$  and 240 vs 890  $\mu\text{g}/\text{m}^3$ , respectively) (Haney, et al., 1992). In a nonmetal mine, personal and area levels of respirable combustible dust in underground production workers and areas were 24% lower after installation of new oxidation catalytic converters (AM: 320 vs 420  $\mu\text{g}/\text{m}^3$ ) (Haney, et al., 1997). Increased underground ventilation resulted in 2–4 times lower EC exposure of nonmetal underground production workers compared to levels under the original mine ventilation conditions (Cohen, et al., 2002). Lower EC levels were reported for samples taken inside the closed cab of production equipment compared to outside the cab (AM: 27 vs 233  $\mu\text{g}/\text{m}^3$ , respectively) (Leeming, et al., 2004). An Australian study reported higher PM<sub>5</sub> levels under extreme load conditions than under normal conditions (400–600 vs 50–400  $\mu\text{g}/\text{m}^3$ , respectively) (Pratt, et al., 1997).

## Railroad transportation

In the US, diesel engines rapidly replaced steam engines in railroad locomotives between 1945 (10% diesel locomotives) and the 1950s (50% and 95% of engines were diesel in 1952 and 1959, respectively) (Garshick, et al., 1987; Garshick, et al., 2004; Laden, et al., 2006). In the 1960s, a second generation of more efficient diesel locomotives, which were reported to be less smoky, was introduced into many of the larger companies (Woskie, et al., 1988). The typical lifespan of a locomotive has been estimated to be more than 40 years, and many of the smaller railroads still use first generation engines built in the 1940s (EPA, 2002). Currently, a typical freight train crew consists of a conductor and engineer in the leading cab (Liukonen, et al., 2002; Verma, et al., 2003), sometimes supplemented with brakemen/switchmen for local or yard jobs (Liukonen, et al., 2002). In passenger trains, conductors

often work in passenger compartments. Prior to the 1980s, tail-end brakemen and firemen also occupied the train (Liukonen, et al., 2002; Verma, et al., 2003; Woskie, et al., 1988 ). The conductor and tail-end brakeman were situated in the caboose, which was used for monitoring of the train, an office for the conductor, shift breaks, and mobile housing. Use of the caboose was discontinued in the mid-1980s due to the emergence of new technologies and reduction in crew size (Liukonen, et al., 2002). Ventilation systems in repair shops for locomotives have greatly improved since the 1950s (Woskie, et al., 1988).

Exposure to DE has been reported for train crew and for maintenance workers of rolling stock and non-rolling stock. The highest EC levels (AM:  $39 \mu\text{g}/\text{m}^3$ ) were reported for maintenance workers in a study that did not measure exposure for other jobs (Groves, et al., 2000) (Table 3). Three studies assessed exposure in both train crew and maintenance workers. Two of these reported higher levels of  $\text{PM}_{10}$  for maintenance workers of rolling stock (AM:  $196 \mu\text{g}/\text{m}^3$  and median:  $148 \mu\text{g}/\text{m}^3$ ) than for the train crew (AM:  $126 \mu\text{g}/\text{m}^3$  and median:  $111 \mu\text{g}/\text{m}^3$ , respectively) (Hammond, et al., 1988; Schenker, et al., 1992). The third study reported low levels of EC (AM  $< 4.6 \mu\text{g}/\text{m}^3$ ) for both job categories (Verma, et al., 2003) and higher NO, but lower NO<sub>2</sub>, levels for the train crew compared to maintenance workers of rolling stock (AM: 0.55 vs 0.26 ppm NO and 0.05 vs 0.10 ppm NO<sub>2</sub>) (Verma, et al., 1999).

Several studies indicate that the location of the exhaust stack in relation to the cab and air flow from outside the cab are important determinants of DE exposure. One study reported detectable EC levels in the trailing locomotive, but not in the front locomotive (Seshagiri, 2003). In addition, the presence of stacks preceding the cab versus not preceding the cab (GM:  $10.1$  vs  $2.5 \mu\text{g}/\text{m}^3$ ) (Liukonen, et al., 2002) and the configuration of the two locomotives in front of the train (both facing forward vs one facing backward:  $4.8$  vs  $13.5 \mu\text{g}/\text{m}^3$ ) (Seshagiri, 2003) were reported to be significant determinants of in-cab EC levels. Significantly higher in-cab EC levels were also reported when windows were open versus closed (GM:  $4.9$  vs  $2.3 \mu\text{g}/\text{m}^3$ ) (Liukonen, et al., 2002) and during summer compared to winter ( $17.1$  vs  $2.9 \mu\text{g}/\text{m}^3$ ) (Seshagiri, 2003). Higher exposure levels to  $\text{PM}_{10}$ , adjusted for cigarette smoke, were reported in the summer compared to winter for yard and passenger engineers/firers and passenger brakemen/conductors, but lower levels were reported for freight engineers/firers, hostlers moving trains in and out of repair shops, and freight and yard brakemen/conductors. In this study, overall, season was a significant determinant (Woskie, et al., 1988). Other determinants were also investigated in this study.  $\text{PM}_{10}$  levels unadjusted for smoking were higher for brakemen/conductors than for firers/engineers (AM:  $112$ – $233$  vs  $74$ – $122 \mu\text{g}/\text{m}^3$ ) (Hammond, et al., 1988). Among brakemen/conductors, the highest  $\text{PM}_{10}$  levels were reported for yard brakemen/conductors and hostlers compared to passenger and freight brakemen/conductors (AM:  $192$ – $233$  vs  $112$ – $128 \mu\text{g}/\text{m}^3$ ), which was attributed to the greater amount of time the former workers spent outdoors near operating trains. Company also significantly affected adjusted  $\text{PM}_{10}$  exposure levels, possibly due to differences in the facility, equipment, maintenance procedures, and fuel (Hammond, et al., 1988; Woskie, et al., 1988). In another study, levels during two 20–30 minute trips in tunnels were 7–110 ppm for CO and 39–70 ppm for NO compared to average 8-hour levels of  $< 1.0$  for CO and 0.11–0.34 ppm for NO during freight operations (Hobbs, et al., 1977).

For repair shop workers, higher personal  $\text{PM}_{10}$  levels were reported for cold compared to warm weather conditions (AM:  $231$ – $254$  vs  $118$ – $127 \mu\text{g}/\text{m}^3$ ) (Hammond, et al., 1988). In addition, area levels of visible smoke, the number of detectable NO<sub>2</sub> samples, and peak CO levels were higher in a roundhouse when the doors were shut than when they were open (Madl, et al., 2002).



## Other off-road uses

Several studies have assessed DE exposure among construction workers. EC levels were higher for underground construction, i.e. tunnels, than for above ground construction (AM: 132–314 vs 4–13  $\mu\text{g}/\text{m}^3$ ) (Table 4). A Swedish study that assessed exposure levels in both types of construction sites reported significantly higher levels in underground locations for all measured agents (AM: 132 vs 13  $\mu\text{g}/\text{m}^3$  for EC, 121 vs 34  $\mu\text{g}/\text{m}^3$  for  $\text{PM}_{10}$  and 0.22 vs 0.02 ppm for  $\text{NO}_2$ ) (Table 4) (Lewne, et al., 2007). A study in the US reported significantly higher EC exposure levels during tunnel construction phases of a large highway construction project for enclosed versus non-enclosed construction sites (AM: 41 vs 24  $\mu\text{g}/\text{m}^3$ ) (Blute, et al., 1999). Other significant determinants of EC exposure were the type of diesel powered machine (crane > generator > lift > earth mover), the distance from the diesel source (less than 10 ft > 10–20 ft > more than 20 ft), and the number of other diesel sources (2 and more > less than 2) (Blute, et al., 1999) (levels not shown in original article). The highest EC levels in this study of mostly above ground heavy and highway construction sites were found during the installation of drop ceiling and wall tiles, concrete pouring, concrete finish work, laying of conduit/pipe in trenches, and excavation work (Woskie, et al., 2002).

Another major off-road use of diesel engines is fork-lift trucks, which may also be powered by propane, gasoline, or electricity. Before 1980, almost all fork-lift trucks used in truck docks were propane or gasoline powered (Zaebst, et al., 1991). Average reported EC levels for dockworkers in the vicinity of diesel powered fork-lifts, including fork-lift truck operators, were generally between 4 and 36  $\mu\text{g}/\text{m}^3$ , except for one study reporting 122  $\mu\text{g}/\text{m}^3$  (Table 4). Significantly lower EC exposure levels in dockworkers were reported when exhaust filters were used compared to no filters (GM: 2 vs 24  $\mu\text{g}/\text{m}^3$ ), and significantly lower  $\text{NO}_2$  levels were reported when an overhead fan was used in the dock compared to no forced ventilation (GM: 0.14 vs 0.21 ppm) (Zaebst, et al., 1992). Another source of DE at docks may be on-road trucks, which back up against the docks for loading and unloading. EC levels reported for docks in which only non-diesel powered fork-lift trucks were used, resulting presumably primarily from on-road trucks, were low (0.9–4.2  $\mu\text{g}/\text{m}^3$ ) (NIOSH, 1993; Zaebst, et al., 1992) compared to the levels shown in Table 4.

Exposure to DE has been assessed for airline baggage screening workers using tugs that may be diesel powered and for mechanics involved in maintenance of equipment and trucks used for refueling of aircraft (AM: 11  $\mu\text{g}/\text{m}^3$  EC) (NIOSH, 1994; NIOSH, 2005). Two studies investigated DE exposure in ship docks. One study reported a mean EC exposure level of 49  $\mu\text{g}/\text{m}^3$  for workers using diesel powered tugs and container lorries for loading and unloading freight from a ferry that was ventilated by opening the bow and stern doors (Groves, et al., 2000). The second study in marine terminals reported an average EC exposure level of 5.7  $\mu\text{g}/\text{m}^3$ , which ranged from 2.5  $\mu\text{g}/\text{m}^3$  for crane operators to 12  $\mu\text{g}/\text{m}^3$  for shop workers (NIOSH, 2006).

## Discussion

Several advisory or regulatory authorities in North America and Europe, including IARC, NIOSH, MSHA, the Health Effects Institute, and the US Environmental Protection Agency (EPA), have concluded that sufficient evidence exists that exposure to DE causes an increased risk of cancer (Rogers, et al., 2005). These evaluations were based on sufficient toxicological animal studies and limited evidence from almost 50 occupational epidemiologic studies. Among other limitations, the lack of quantitative exposure assessment has consistently been cited as a fundamental problem in determining causality from the existing epidemiological studies (Rogers, et al., 2005). The purpose of this review was to provide a comprehensive overview of quantitative occupational exposure levels to

DE that will allow for more accurate and consistent occupational exposure assessments in population-based epidemiologic studies.

For EC, the highest exposure levels were reported for underground mining (27–658  $\mu\text{g}/\text{m}^3$ ), tunnel construction (132–314  $\mu\text{g}/\text{m}^3$ ), and underground mine maintenance workers (53–144  $\mu\text{g}/\text{m}^3$ ). For maintenance workers of on-road and railroad equipment, distribution workers, fire fighters, and ship dock workers, exposure levels generally ranged from ND to 50  $\mu\text{g}/\text{m}^3$ . Relatively low levels were reported for drivers of on-road vehicles, train crews, above ground mining, parking attendants, vehicle testers, utility service workers, above ground construction, and airline ground personnel (<25  $\mu\text{g}/\text{m}^3$ ). For airline personnel, jet exhaust may be another source of EC and more research is needed to investigate its contribution (Schauer, 2003). EC is currently the preferred surrogate for DE in industries other than coal mines (Leeming, et al., 2004), since it is relative simple to measure, has few chemical interferences and is the major component of diesel particulate matter (Groves, et al., 2000; Schauer, 2003).

There was little information available on  $\text{PM}_{10}$  to compare with the EC levels. Exposure levels of miners and underground construction workers were highest (154–1600 and 121  $\mu\text{g}/\text{m}^3$ , respectively), followed by mechanics, above ground construction workers, and taxi drivers (10–35  $\mu\text{g}/\text{m}^3$ ).  $\text{PM}_{10}$  has only a few interferences from non-diesel sources, i.e. oil mist and cigarette smoke (Hammond, et al., 1988).  $\text{PM}_{10}$  is a less suitable surrogate for DE since it is generated from more non-diesel sources, i.e. oil and grease mists, cigarette smoke, emissions from other combustion sources, and respirable inorganic matter such as mechanically aerosolized geological and fibrous materials (Hammond, et al., 1988). These non-diesel sources are a likely explanation for the reported  $\text{PM}_{10}$  levels that were substantially higher than  $\text{PM}_{10}$  levels in all situations. Nonetheless, for  $\text{PM}_{10}$ , the highest levels also were reported for workers in underground mining and underground construction (710–3637 and 1160–1700, respectively).

For the gases, the highest mean levels generally were reported for workers in underground mining and underground construction. Similar to PM, the pattern of the gases among industries was generally consistent with the EC levels. However, relatively high mean concentrations for some of the gases also were reported in situations where reported EC levels were low, e.g. for DE exposed airline personnel, train crews, and utility service workers. These higher levels are likely the result of emissions from other combustion sources.

The results of this review suggest that enclosure of the work site and the type of diesel equipment used are the most important determinants affecting occupational DE exposure. Highest levels were found in underground mining, maintenance, and construction, where heavy equipment is used in enclosed underground work sites. Situations for which intermediate exposure levels were reported mostly involved smaller equipment, probably run intermittently, in above ground (semi-)enclosed areas that were more easily ventilated by natural or mechanical ventilation, i.e. mechanics in a shop, emergency workers in fire stations, distribution workers at a dock, and workers loading/unloading vehicles inside a ferry. Determinants that have been repeatedly reported for both above and underground (semi-)enclosed situations were ventilation (Cohen, et al., 2002; Davis, et al., 2006; Hammond, et al., 1988; Madl, et al., 2002; Sauvain, et al., 2003; Zaebs, et al., 1992; Zaebs, et al., 1991) and the use of exhaust after treatment devices (Ambs, et al., ; Haney, et al., 1992; Haney, et al., 1997; Roegner, et al., 2002; Zaebs, et al., 1992). Lowest levels were found for workers in enclosed areas separated from the source or for workers who were outside. Airflow from outside the train or truck cab was reported to result in higher exposure levels for train crew and on-road drivers than exposure levels within a closed cab (Davis, et

al., 2007; Liukonen, et al., 2002; Seshagiri, 2003; Zaebs, et al., 1991), suggesting that DE exposure in these situations occurs mostly via the outdoor air. The railroad studies indicated that the exposure is derived from preceding stacks of the same train (Liukonen, et al., 2002; Seshagiri, 2003). For drivers of on-road vehicles, higher levels were reported for inner city drivers than for drivers in rural or suburban areas, suggesting that emissions from other vehicles are probably responsible for most of the exposure (Garshick, et al., 2002; Lewne, et al., 2006).

Assessing occupational exposures in epidemiological studies in the general population is challenging. For chronic diseases such as cancer, the relevant exposure periods are usually decades ago, and exposure measurements for the relevant exposure period are often not available. In addition, exposures can vary widely depending on individual work environments. Thus, the availability of a comprehensive database of historical quantitative exposure levels including determinants of exposure is likely to result in a more accurate and consistent exposure assessment than when the assessment is based only on expert judgment.

However, there are some limitations to this approach. Because DE is a complex mixture of compounds, several agents were selected, complicating comparison across studies focusing on different agents. In addition, the composition of DE varies with engine technology, fuel type, operating conditions, and the presence of emission control systems, which have all changed over time (EPA, 2002; Lloyd, et al., 2001).  $PM_{10}$  and the gases were selected to investigate time trends, since the more specific surrogates of DE, such as EC, were not developed until the 1990s. Recently, more advanced chemical techniques are being developed. However, these are not yet suitable for application in epidemiological and exposure studies because of the extensive number of samples and low air volume of the samples typical in these studies (Schauer, 2003). Regulation of emissions has decreased emission levels (Bunn, et al., 2002; Laden, et al., 2006), yet the use of diesel engines has increased. However, not enough exposure data were available to assess the effect of these changes. Consequently, the incorporation of time trends in exposure assessment will be problematic. Another limitation of the complex composition of DE, is that the relevant toxic agent, which varies by health effect (Scheepers, et al., 1992), may not be proportional to the chosen agent of study.

A further limitation of using published literature is the extraction and interpretation of exposure information from reports written by different authors for different purposes. The description of the measured jobs, the number of measurements, the duration of the measurements, and the exposure conditions was often unclear or absent. In addition, published reports may have been biased towards worst case scenarios and may not represent what is typical for the industry with regard to both the types of jobs reported and the concentrations measured. Finally, measurements on other industrial uses, such as farming and the military, have not been reported.

In spite of these limitations, contrast in exposure levels was found when comparing different jobs and industries, and several determinants of exposure have been identified. The data described in this study can be used to assess exposure levels based on job and industry title and certain exposure characteristics in population-based epidemiologic studies. Furthermore, these data can guide future exposure assessment efforts as well as the selection of study populations for future epidemiologic studies.

## Acknowledgments

The authors would like to thank Dr. Mustafa Dosemeci for conducting the literature search and Mr Dennis Zaebs for providing NIOSH Health Hazard Evaluation reports. This research was supported by the Intramural Research Program of the National Cancer Institute.

## References

- Adelroth E, Hedlund U, Blomberg A, Helleday R, Ledin MC, Levin JO, Pourazar J, Sandstrom T, Jarvholm B. Airway inflammation in iron ore miners exposed to dust and diesel exhaust. *Eur Respir J*. 2006; 27(4):714–719. [PubMed: 16455836]
- Aitchison, J.; Brown, JAC. *The lognormal distribution*. Cambridge University Press; Cambridge, England: 1969.
- Ambs, JL.; Cantrell, BK.; Watts, WF.; Olson, KS. Report of investigations 9508. Twin Cities, MN: Bureau of Mines; 1994. Evaluation of a disposable diesel exhaust filter for permissible mining machines.
- Ames RG, Attfield MD, Hankinson JL, Hearl FJ, Reger RB. Acute respiratory effects of exposure to diesel emissions in coal miners. *Am Rev Respir Dis*. 1982; 125(1):39–42. [PubMed: 7065507]
- Attfield, MD. The effect of exposure to silica and diesel exhaust in underground metal and nonmetal miners. *Industrial hygiene for mining and tunneling. Proceedings of a topical symposium*; Denver, Co. 1978.
- Bakke B, Stewart P, Ulvestad B, Eduard W. Dust and gas exposure in tunnel construction work. *AIHAJ*. 2001; 62(4):457–465. [PubMed: 11549139]
- Blute NA, Woskie SR, Greenspan CA. Exposure characterization for highway construction. Part I: Cut and cover and tunnel finish stages. *Appl Occup Environ Hyg*. 1999; 14(9):632–641. [PubMed: 10510526]
- Boffetta, P.; Cherrie, J.; Hughson, G.; Pitard, A. Cancer risk from diesel emissions exposure in Central and Eastern Europe: A feasibility study. In: McLellan, G., editor. *HEI special report. Research directions to improve estimates of human exposure and risk from diesel exhaust. A special report of the Institute's diesel epidemiology working group*. Health Effects Institute; Boston, MA: 2002. p. 57-78.
- Bunn WB 3rd, Valberg PA, Slavin TJ, Lapin CA. What is new in diesel. *Int Arch Occup Environ Health*. 2002; 75(Suppl):S122–132. [PubMed: 12397423]
- Burgess JL, Fleming JE, Mulenga EM, Josyula A, Hysong TA, Joggerst PJ, Kurzius-Spencer M, Miller HB. Acute changes in sputum IL–10 following underground exposure to diesel exhaust. *Clin Toxicol*. 2007; 45(3):255–260.
- Cantrell BK, Rubow KL, Watts WF, Carlson DH. Pollutant levels in underground coal mines using diesel equipment. *Transactions of society for mining, metallurgy and exploration*. 1991; 290:1901–1907.
- Cohen HJ, Borak J, Hall T, Sirianni G, Chemerynski S. Exposure of miners to diesel exhaust particulates in underground nonmetal mines. *AIHAJ*. 2002; 63(5):651–658.
- Commins BT, Waller RE, Lawther PJ. Air pollution in diesel bus garages. *Br J Ind Med*. 1957; 14(4): 232–239. [PubMed: 13471867]
- Dahmann D, Monz C, Sonksen H. Exposure assessment in German potash mining. *Int Arch Occup Environ Health*. 2007; 81(1):95–107. [PubMed: 17569074]
- Davis ME, Smith TJ, Laden F, Hart JE, Ryan LM, Garshick E. Modeling particle exposure in U.S. trucking terminals. *Environ Sci Technol*. 2006; 40(13):4226–4232. [PubMed: 16856739]
- Davis ME, Smith TJ, Laden F, Hart JE, Blicharz AP, Reaser P, Garshick E. Driver exposure to combustion particles in the U.S. Trucking industry. *J Occup Environ Hyg*. 2007; 4(11):848–854. [PubMed: 17885912]
- DieselNet. Emission standards. Ecopoint Inc; 2008. <http://www.dieselnet.com/standards/us/ohs.php>
- Echt A, Sheehy J, Blade L. Exposure to diesel exhaust emissions at three fire stations: evaluation and recommended controls. *Appl Occup Environ Hyg*. 1995; 10(5):431–438.
- EPA. Health assessment document for diesel engine exhaust. EPA/600/8-90/057F. Washington DC: Environmental Protection Agency; 2002.
- Froines JR, Hinds WC, Duffy RM, Lafuente EJ, Liu WC. Exposure of firefighters to diesel emissions in fire stations. *AIHAJ*. 1987; 48(3):202–207.
- Gamble, J.; Jones, W.; Hudak, J.; Merchant, J. Acute changes in pulmonary function in salt miners. In: Kelley, WD., editor. *Industrial hygiene for mining and tunneling; Proceedings of a Topical*

- Symposium; November 6–7, 1978; Denver, Co: American Conference of Governmental Industrial Hygienists; 1978. p. 119-128.
- Gamble J, Jones W, Minshall S. Epidemiological-environmental study of diesel bus garage workers: acute effects of NO<sub>2</sub> and respirable particulate on the respiratory system. *Environ Res.* 1987; 42(1):201–214. [PubMed: 2433131]
- Garshick E, Schenker MB, Munoz A, Segal M, Smith TJ, Woskie SR, Hammond SK, Speizer FE. A case-control study of lung cancer and diesel exhaust exposure in railroad workers. *Am Rev Respir Dis.* 1987; 135(6):1242–1248. [PubMed: 3592400]
- Garshick, E.; Smith, TJ.; Laden, F. Quantitative assessment of lung cancer risk from diesel exhaust exposure in the US trucking industry: a feasibility study. In: McLellan, G., editor. HEI special report. Research directions to improve estimates of human exposure and risk from diesel exhaust. A special report of the Institute's diesel epidemiology working group. Health Effects Institute; Boston, MA: 2002. p. 113-150.
- Garshick E, Laden F, Hart JE, Rosner B, Smith TJ, Dockery DW, Speizer FE. Lung cancer in railroad workers exposed to diesel exhaust. *Environ Health Perspect.* 2004; 112(15):1539–1543. [PubMed: 15531439]
- Groves J, Cain JR. A survey of exposure to diesel engine exhaust emissions in the workplace. *Ann Occup Hyg.* 2000; 44(6):435–447. [PubMed: 10963708]
- Hammond SK, Smith TJ, Woskie SR, Leaderer BP, Bettinger N. Markers of exposure to diesel exhaust and cigarette smoke in railroad workers. *AIHAJ.* 1988; 49(10):516–522.
- Haney RA. Diesel particulate exposures in underground mines. *Mining engineering.* 1992; 44(2):173–176.
- Haney, RA.; Ondrey, RS.; Atchison, DJ. New Technology in Mine Health and Safety. Chapter 15 - Mine Dust and Diesel Emission. 1992. Control of diesel particulate emissions in underground coal mines; p. 143-151.
- Haney, RA.; Fields, KG.; Vail, SG. Evaluation of diesel particulate exposures and control technology in a nonmetal mine. In: Ramani, RV., editor. 6th International mine ventilation congress. Pittsburgh, PA: Society for Mining, Metallurgy, and Exploration, Inc; 1997. p. 141-143.
- Haney RA, Saseen GP, Waytulonis RW. An overview of diesel particulate exposures and control technology in the U.S. mining industry. *Appl Occup Environ Hyg.* 1997; 12(12):1013–1018.
- HEI. A special report of the institute's diesel epidemiology working group. WA 754 R432. Boston, MA: Health Effects Institute; 2002. Research directions to improve estimates of human exposure and risk from diesel exhaust.
- Hein MJ, Waters MA, van Wijngaarden E, Deddens JA, Stewart PA. Issues when modeling benzene, toluene, and xylene exposures using a literature database. *J Occup Environ Hyg.* 2008; 5(1):36–47. [PubMed: 18041643]
- Hobbs, JR.; Walter, RA.; Hard, T.; Devoe, D. Train generated air contaminants in the train crew's working environment. Cambridge, MA: US Department of Transportation; 1977.
- Hornung, RW.; Reed, LD. *Appl Occup Environ Hyg.* Vol. 5. 1990. Estimation of average concentration in the presence of non-detectable values; p. 48-51.
- IARC. Diesel and engine exhausts and some nitroarenes. Vol. 46. Lyon, France: International Agency for Research on Cancer; 1989. IARC Monographs on the evaluation of carcinogenic risks to humans.
- Kauppinen T, Toikkanen J, Pedersen D, Young R, Ahrens W, Boffetta P, Hansen J, Kromhout H, Maqueda Blasco J, Mirabelli D, de la Orden-Rivera V, Pannett B, Plato N, Savela A, Vincent R, Kogevinas M. Occupational exposure to carcinogens in the European Union. *Occup Environ Med.* 2000; 57(1):10–18. [PubMed: 10711264]
- Lachtman DS. Mining health hazards of diesel exhaust. *Ann Am Conf Gov Ind Hyg.* 1983; 4:63–71.
- Laden F, Hart JE, Eschenroeder A, Smith TJ, Garshick E. Historical estimation of diesel exhaust exposure in a cohort study of U.S. railroad workers and lung cancer. *Cancer Causes Control.* 2006; 17(7):911–919. [PubMed: 16841258]
- Leeming, JR.; Dabill, DW. Measuring exposure to diesel engine exhaust emissions in UK coal and non-coal mines. In: Ganguli, R.; Bandopadhyay, S., editors. Mine Ventilation Proceedings of the

- 10th US/North American mine ventilation symposium. Anchorage, AK: AA Balkema Publishers; 2004.
- Lewne M, Nise G, Lind ML, Gustavsson P. Exposure to particles and nitrogen dioxide among taxi, bus and lorry drivers. *Int Arch Occup Environ Health*. 2006; 79(3):220–226. [PubMed: 16283363]
- Lewne M, Plato N, Gustavsson P. Exposure to particles, elemental carbon and nitrogen dioxide in workers exposed to motor exhaust. *Ann Occup Hyg*. 2007; 51(8):693–701. [PubMed: 17921238]
- Liukonen LR, Grogan JL, Myers W. Diesel particulate matter exposure to railroad train crews. *AIHAJ*. 2002; 63(5):610–616.
- Lloyd AC, Cackette TA. Diesel engines: environmental impact and control. *J Air Waste Manag Assoc*. 2001; 51(6):809–847. [PubMed: 11417675]
- Madl AK, Paustenbach DJ. Airborne concentrations of benzene due to diesel locomotive exhaust in a roundhouse. *J Toxicol Environ Health A*. 2002; 65(23):1945–1964. [PubMed: 12490041]
- McDonald JD, Zielinska B, Sagebiel JC, McDaniel MR. Characterization of fine particle material in ambient air and personal samples from an underground mine. *Aerosol Science and Technology*. 2002; 36:1033–1044.
- MSHA. Diesel particulate matter exposure of underground metal and nonmetal miners; Proposed rule 30 CRF Part 57. Arlington, VA: Mine Safety and Health Administration; 1998. p. 28924-29012.
- MSHA. MSHA's report on data collected during a joint MSHA/industry study of DPM levels in underground metal and nonmetal mines. Arlington, VA: Mine Safety and Health Administration; 2003.
- NIOSH. National occupational exposure survey, 1981–1983; estimated total and female employees, actual observation and trade named exposure to products of combustion —diesel fuels. Cincinnati, OH: National Institute for Occupational Safety and Health; 1983.
- NIOSH. Ryder/pie trucking lines, Cincinnati, OH. NIOSH Preliminary Industrial Hygiene Survey. Cincinnati, OH: National Institute for Occupational Safety and Health; 1986.
- NIOSH. Morton Salt Company. NIOSH Health Hazard Evaluation Report 88-388-2155. Cincinnati, OH: National Institute for Occupational Safety and Health; 1991.
- NIOSH. ASARCO New Market/Young mines, Mascot, Tennessee. NIOSH Health Hazard Evaluation Report 88-108-2146. Cincinnati, OH: National Institute for Occupational Safety and Health; 1991.
- NIOSH. International Salt Company, Avery Island, Louisiana. . NIOSH Health Hazard Evaluation Report 88-389-2147. Cincinnati, OH: National Institute for Occupational Safety and Health; 1991.
- NIOSH. ASARCO - Troy unit mine, Troy, Montana. NIOSH Health Hazard Evaluation Report 88-104-2207. Cincinnati, OH: National Institute for Occupational Safety and Health; 1992.
- NIOSH. Empire distributors, Inc. Atlanta, Georgia . NIOSH Health Hazard Evaluation Report 92-226-2269. Cincinnati, OH: National Institute for Occupational Safety and Health; 1993.
- NIOSH. Morton Salt Company, Weeks Island, Louisiana. . NIOSH Health Hazard Evaluation Report 88-391-2156. Cincinnati, OH: National Institute for Occupational Safety and Health; 1993.
- NIOSH. Ogden Aviation, Newark Airport. . NIOSH Health Hazard Evaluation Report 92-0288-2454. Cincinnati, OH: National Institute for Occupational Safety and Health; 1994.
- NIOSH. Wolfeboro Public Safety Building, Wolfeboro, New Hampshire. NIOSH Health Hazard Evaluation Report 98-0152-2729. Cincinnati, OH: National Institute for Occupational Safety and Health; 1998.
- NIOSH. San Francisco Municipal Railway, Flynn Facility San Francisco, California. NIOSH Health Hazard Evaluation Report 98-0041-2741. Cincinnati, OH: National Institute for Occupational Safety and Health; 1998.
- NIOSH. Racine fire department, Racine, Wisconsin . NIOSH Health Hazard Evaluation Report 97-0304-2695. Cincinnati, OH: National Institute for Occupational Safety and Health; 1998.
- NIOSH. NIOSH Health Hazard Evaluation Report 2005-0091-2957. Cincinnati, OH: National Institute for Occupational Safety and Health; 2005. Air contaminant and noise exposures among transportation security administration baggage screeners at four international airports.
- NIOSH. Joint pacific marine safety code committee San Francisco, California. NIOSH Health Hazard Evaluation report 2003-0246-3013. Cincinnati, OH: National Institute for Occupational Safety and Health; 2006.

- Pratt SL, Grainger AP, Todd J, Meena GG, Rogers AJ, Davies B. Evaluation and control of employee exposure to diesel particulate at several Australian coal mines. *Appl Occup Environ Hyg.* 1997; 12(12):1032–1037.
- Ramachandran G, Paulsen D, Watts W, Kittelson D. Mass, surface area and number metrics in diesel occupational exposure assessment. *J Environ Monit.* 2005; 7(7):728–735. [PubMed: 15986054]
- Reger R, Hancock J, Hankinson J, Hearl F, Merchant J. Coal miners exposed to diesel exhaust emissions. *Ann Occup Hyg.* 1982; 26(1–4):799–815. [PubMed: 7181308]
- Ris CUS. EPA health assessment for diesel engine exhaust: a review. *Inhal Toxicol.* 2007; 19(Suppl 1):229–239. [PubMed: 17886071]
- Roegner K, Sieber WK, Echt A. Evaluation of diesel exhaust controls. *Appl Occup Environ Hyg.* 2002; 17(1):1–7. [PubMed: 11800399]
- Rogers A, Davies B. Diesel particulates--recent progress on an old issue. *Ann Occup Hyg.* 2005; 49(6):453–456. [PubMed: 15964880]
- Sauvain JJ, Vu Duc T, Guillemin M. Exposure to carcinogenic polycyclic aromatic compounds and health risk assessment for diesel-exhaust exposed workers. *Int Arch Occup Environ Health.* 2003; 76(6):443–455. [PubMed: 12750904]
- Schauer JJ. Evaluation of elemental carbon as a marker for diesel particulate matter. *J Expo Anal Environ Epidemiol.* 2003; 13(6):443–453. [PubMed: 14603345]
- Scheepers PT, Bos RP. Combustion of diesel fuel from a toxicological perspective. II. Toxicity. *Int Arch Occup Environ Health.* 1992; 64(3):163–177. [PubMed: 1383163]
- Scheepers PT, Micka V, Muzyka V, Anzion R, Dahmann D, Poole J, Bos RP. Exposure to dust and particle-associated 1-nitropyrene of drivers of diesel-powered equipment in underground mining. *Ann Occup Hyg.* 2003; 47(5):379–388. [PubMed: 12855488]
- Schenker MB, Kado NY, Hammond SK, Samuels SJ, Woskie SR, Smith TJ. Urinary mutagenic activity in workers exposed to diesel exhaust. *Environ Res.* 1992; 57(2):133–148. [PubMed: 1373681]
- Seshagiri B. Exposure to diesel exhaust emissions on board locomotives. *AIHAJ.* 2003; 64(5):678–683.
- Silverman DT. Is diesel exhaust a human lung carcinogen? *Epidemiology.* 1998; 9(1):4–6. [PubMed: 9430259]
- Stanevich RS, Hintz P, Yereb D, Dosemeci M, Silverman DT. Elemental carbon levels at a potash mine. *Appl Occup Environ Hyg.* 1997; 12(12):1009–1012.
- Steenland K, Deddens J, Stayner L. Diesel exhaust and lung cancer in the trucking industry: exposure-response analyses and risk assessment. *Am J Ind Med.* 1998; 34(3):220–228. [PubMed: 9698990]
- Steenland NK, Silverman DT, Hornung RW. Case-control study of lung cancer and truck driving in the Teamsters Union. *Am J Public Health.* 1990; 80(6):670–674. [PubMed: 1693040]
- Ulfvarson U, Alexandersson R, Dahlqvist M, Ekholm U, Bergstrom B. Pulmonary function in workers exposed to diesel exhausts: the effect of control measures. *Am J Ind Med.* 1991; 19(3):283–289. [PubMed: 1706909]
- Verma DK, Shaw L, Julian J, Smolyne K, Wood C, Shaw D. A comparison of sampling and analytical methods for assessing occupational exposure to diesel exhaust in a railroad work environment. *Appl Occup Environ Hyg.* 1999; 14(10):701–714. [PubMed: 10561882]
- Verma DK, Finkelstein MM, Kurtz L, Smolyne K, Eyre S. Diesel exhaust exposure in the Canadian railroad work environment. *Appl Occup Environ Hyg.* 2003; 18(1):25–34. [PubMed: 12650546]
- Waller RE, Hampton L, Lawther PJ. A further study of air pollution in diesel bus garages. *Br J Ind Med.* 1985; 42(12):824–830. [PubMed: 4074654]
- Watts, WF.; Cantrell, BK.; Ams, JL.; Rubow, KL. Proceedings: Bureau of mines information and technology transfer seminar. Minneapolis, MN: Bureau of Mines; 1992. Diesel exhaust aerosol levels in underground coal mines.
- Wheatley AD, Sadhra S. Occupational exposure to diesel exhaust fumes. *Ann Occup Hyg.* 2004; 48(4):369–376. [PubMed: 15148050]
- Wheeler, RW.; Hearl, PEFJ.; McCawley, M. Health effects of diesel engine emissions: Proceedings of an international symposium. USEPA-600.9-80-057b. Environmental Protection Agency; 1980. An

industrial hygiene characterization of exposures to diesel emissions in an underground coal mine; p. 1136-1147.

Whittaker LS, MacIntosh DL, Williams PL. Employee exposure to diesel exhaust in the electric utility industry. *AIHAJ*. 1999; 60(5):635–640.

Woskie SR, Smith TJ, Hammond SK, Schenker MB, Garshick E, Speizer FE. Estimation of the diesel exhaust exposures of railroad workers: II. National and historical exposures. *Am J Ind Med*. 1988; 13(3):395–404. [PubMed: 3281456]

Woskie SR, Smith TJ, Hammond SK, Schenker MB, Garshick E, Speizer FE. Estimation of the diesel exhaust exposures of railroad workers: I. Current exposures. *Am J Ind Med*. 1988; 13(3):381–394. [PubMed: 3354586]

Woskie SR, Kalil A, Bello D, Virji MA. Exposures to quartz, diesel, dust, and welding fumes during heavy and highway construction. *AIHAJ*. 2002; 63(4):447–457.

Zaebst D, Stern F, Heitbrink W, Cooper T. Evaluation of techniques for reducing diesel forklift emissions. *Appl Occup Environ Hyg*. 1992; 7(1):17–18.

Zaebst DD, Clapp DE, Blade LM, Marlow DA, Steenland K, Hornung RW, Scheutzle D, Butler J. Quantitative determination of trucking industry workers' exposures to diesel exhaust particles. *AIHAJ*. 1991; 52(12):529–541.



Table 1

Occupational exposure measurements to diesel exhaust from on-road vehicles: elemental carbon (EC,  $\mu\text{g}/\text{m}^3$ ), submicron and respiratory particulate matter (PM<sub>S</sub> and PM<sub>R</sub>,  $\mu\text{g}/\text{m}^3$ ), and CO, NO and NO<sub>2</sub> (ppm)

Description	Agent	Duration	n	AM (SD)	GM (GSD)	Location	Year	Reference
<u>Drivers</u>								
Truck – local	EC <sub>S</sub>	>4	56	5 (0.9)	0.9 (4.0)	US	1980s	(Zaebst, et al., 1991)
Truck – local	EC <sub>S</sub>	>4	576 (a)	2 (2.3)	1 (2.8)	US	2001–2005	(Davis, et al., 2007)
Truck – local	EC <sub>R</sub>	>4	5	7 <sup>e</sup>	6 (1.6)	US	1999	(Garshick, et al., 2002)
Truck – local	EC <sub>NI</sub>	>4	4 (a)	5 (0.1)	5 (1.0)	US	1985	(NIOSH, 1986)
Truck - long haul	EC <sub>S</sub>	>4	72	5 (0.4)	0.4 (3.8)	US	1980s	(Zaebst, et al., 1991)
Truck - long haul	EC <sub>S</sub>	>4	349 (a)	1 (0.8)	1 (2.3)	US	2001–2005	(Davis, et al., 2007)
Truck - long haul	EC <sub>R</sub>	>4	5	5 <sup>e</sup>	4 (2.0)	US	1999	(Garshick, et al., 2002)
Truck - long haul	EC <sub>NI</sub>	>4	4 (a)	22 (13.2)	19 (2.0)	US	1985	(NIOSH, 1986)
Truck	EC <sub>I</sub>	1->4	3	10 (6.0)	9 (1.8)	US	1992	(NIOSH, 1993)
Bus	EC <sub>R</sub>	>4	5	10 <sup>e</sup>	9 (1.3)	Estonia	2002 (p)	(Boffetta, et al., 2002)
Bus	EC <sub>R</sub>	>4	39	2.0 (1.3)	1.4 (3.3)	US	2002 (p)	(Ramachandran, et al., 2005)
Bus	EC <sub>I</sub>	>4	4	2->LOD: 11–20		US	1998	(NIOSH, 1998)
Bus and truck <sup>∞</sup>	EC <sub>I</sub>	>4	20	11 <sup>e</sup>	6 (2.9)	Sweden	2002–2004	(Lewne, et al., 2007)
Taxi <sup>∞</sup>	EC <sub>I</sub>	>4	8	8 <sup>e</sup>	7 (1.6)	Sweden	2002–2004	(Lewne, et al., 2007)
<u>Mechanics</u>								
Truck	EC <sub>S</sub>	>4	80	27 (4.1)	4 (12.1)	US	1980s	(Zaebst, et al., 1991)
Truck	EC <sub>R</sub>	>4	10	4 <sup>e</sup>	4 (1.6)	US	1999	(Garshick, et al., 2002)
Ambulance depot	EC <sub>R</sub>	>4	3	31	29 (1.6)	UK	2000(p)	(Groves, et al., 2000)
Bus	EC <sub>R</sub>	>4	53	39	31 (2.1)	UK	2000(p)	(Groves, et al., 2000)
Bus	EC <sub>R</sub>	>4	15	39 <sup>e</sup>	38 (1.3)	Estonia	2002 (p)	(Boffetta, et al., 2002)
Truck/bus (+inspection)	EC <sub>I</sub>	>4	40	21 <sup>e</sup>	11 (3.2)	Sweden	2002–2004	(Lewne, et al., 2007)
Bus	EC <sub>I</sub>	>4	4	ND	ND	US	1998	(NIOSH, 1998)
<u>Others</u>								
Firefighter	EC <sub>I</sub>	>4	27	24 (max)		US	2002(p)	(Roegner, et al., 2002)

Description	Agent	Duration	n	AM (SD)	GM (GSD)	Location	Year	Reference
Firefighter	EC <sub>1</sub>	>4	18	40 (20.3)	35 (1.7)	US	1995(p)	(Echt, et al., 1995)
Firefighter	EC <sub>1</sub>	>4	12	10 (max)		US	1997	(NIOSH, 1998)
Firefighter	EC <sub>1</sub>	<1	8	ND	ND	US	1998	(NIOSH, 1998)
Service worker bus	EC <sub>1</sub>	>4	4	2>LOD: 0.3–15		US	1998	(NIOSH, 1998)
Vehicle testing	EC <sub>R</sub>	>4	11	11	11 (1.8)	UK	2000(p)	(Groves, et al., 2000)
Parking attendant (booth)	EC <sub>R</sub>	>4	34 (a)	1.1 (0.6)	1.1 (1.8)	US	2002 (p)	(Ramachandran, et al., 2005)
<u>Drivers</u>								
Taxi <sup>∞</sup>	PM <sub>S</sub>	>4	8	12 <sup>e</sup>	11 (1.3)	Sweden	2002–2004	(Lewne, et al., 2007)
Bus and truck <sup>∞</sup>	PM <sub>S</sub>	>4	20	15 <sup>e</sup>	14 (1.6)	Sweden	2002–2004	(Lewne, et al., 2007)
Truck – local	PM <sub>R</sub>	>4	5	129 <sup>e</sup>	120 (1.5)	US	1999	(Garshick, et al., 2002)
Truck – local	PM <sub>R</sub>	>4	545 (a)	28 (39)	20 (2.1)	US	2001–2005	(Davis, et al., 2007)
Truck - long haul	PM <sub>R</sub>	>4	4	56 <sup>e</sup>	55 (1.2)	US	1999	(Garshick, et al., 2002)
Truck - long haul	PM <sub>R</sub>	>4	334 (a)	53 (328)	23 (2.5)	US	2001–2005	(Davis, et al., 2007)
Bus	PM <sub>R</sub>	>4	5	600 <sup>e</sup>	580 (1.5)	Estonia	2002 (p)	(Boffetta, et al., 2002)
<u>Mechanics</u>								
Truck/bus (+inspection)	PM <sub>S</sub>	>4	40	28 <sup>e</sup>	23 (1.9)	Sweden	2002–2004	(Lewne, et al., 2007)
Truck	PM <sub>R</sub>	>4	10	203 <sup>e</sup>	152 (2.1)	US	1999	(Garshick, et al., 2002)
Bus	PM <sub>R</sub>	>4	15	1100 <sup>e</sup>	1020 (1.6)	Estonia	2002 (p)	(Boffetta, et al., 2002)
Bus	PM <sub>R</sub>	NI	232	240 (260)		US	1987 (p)	(Gamble, et al., 1987)
Bus	PM <sub>R</sub>	>4	41	267	224 (1.8)	UK	2000(p)	(Groves, et al., 2000)
Ambulance depot	PM <sub>R</sub>	>4	3	127	118 (1.6)	UK	2000(p)	(Groves, et al., 2000)
<u>Others</u>								
Vehicle testing	PM <sub>R</sub>	>4	10	156	149 (1.4)	UK	2000(p)	(Groves, et al., 2000)
<u>Driver</u>								
Truck – local	NO	>4	4 (a)	0.23 (0.05)	0.22 (1.3)	US	1985	(NIOSH, 1986)
Truck - long haul	NO	>4	4 (a)	0.27 (0.10)	0.25 (1.5)	US	1985	(NIOSH, 1986)
<u>Driver</u>								

Description	Agent	Duration	n	AM (SD)	GM (GSD)	Location	Year	Reference
Taxi <sup>∞</sup>	NO <sub>2</sub>	>4	12	0.03 <sup>e</sup>	0.02 (0.7)	Sweden	2002–2004	(Lewne, et al., 2007)
Bus and truck <sup>∞</sup>	NO <sub>2</sub>	>4	30	0.03 <sup>e</sup>	0.03 (0.7)	Sweden	2002–2004	(Lewne, et al., 2007)
Truck	NO <sub>2</sub>	>4	40	0.04 (0.02)		Sweden	1997–1999	(Lewne, et al., 2006)
Taxi	NO <sub>2</sub>	>4	20	0.03 (0.01)		Sweden	1997–1999	(Lewne, et al., 2006)
Bus	NO <sub>2</sub>	>4	42	0.03 (0.01)		Sweden	1997–1999	(Lewne, et al., 2006)
<u>Mechanics</u>								
Truck/bus (+inspection)	NO <sub>2</sub>	>4	60	0.05 <sup>e</sup>	0.05 (0.9)	Sweden	2002–2004	(Lewne, et al., 2007)
Bus	NO <sub>2</sub>	NI	232	0.24 (0.26)		US	1987 (p)	(Gamble, et al., 1987)

S = submicron, R = respirable, I = inhalable; NI: not indicated; (a): area sample representative of personal exposure;

<sup>e</sup>AM estimated from GM and GSD or from range; (p): publication year, sampling year not available;

<sup>∞</sup> Mostly diesel powered vehicles

**Table 2**

Occupational exposure measurements of diesel exhaust in the mining industry: elemental carbon (EC,  $\mu\text{g}/\text{m}^3$ ), submicron and respiratory particulate matter (PM<sub>S</sub> and PM<sub>R</sub>,  $\mu\text{g}/\text{m}^3$ ), and CO, NO and NO<sub>2</sub> (ppm)

Description	Agent	Duration	n	AM (SD)	GM (GSD)	Location	Year	Ref
<u>Underground</u>								
Production (NM/NI)	EC <sub>S</sub>	1->4	13	163 (141)	84 (4.3)	US	2001–2002	
Production (NM)	EC <sub>R</sub>	NI	6 (a)	148 (136)	85 (3.5)	UK	2004(p)	(Leeming, et al., 2004)
Production (NM)	EC <sub>R</sub>	>4	343	202 (32–144)	111 (1.4–4.8)	US	2002(p)	(Cohen, et al., 2002)
Production (NM)	EC <sub>S</sub>	>4	38	219 (65–193)		US	1997(p)	(Stanevich, et al., 1997)
Production (C)	EC <sub>R</sub>	>4	4	241 <sup>e</sup>	202 (1.8)	Estonia	2002 (p)	(Boffetta, et al., 2002)
Production (M)	EC <sub>R</sub>	>4	15	637 (75–508)		US	1999	(McDonald, et al., 2002)
Production (NI)	EC <sub>I</sub>	<1–4	12	538 (512)		US	2007 (p)	(Burgess, et al., 2007)
Maintenance (NM)	EC <sub>S</sub>	>4	8	53 (46)		US	1997(p)	(Stanevich, et al., 1997)
Maintenance (NM)	EC <sub>R</sub>	>4	269	144 (17–462)	66 (1.7–4.6)	US	2002(p)	(Cohen, et al., 2002)
Mining, NS (C)	EC <sub>R</sub>	NI	7 (a)	66 (28)	62 (1.5)	UK	2004(p)	(Leeming, et al., 2004)
Mining, NS (M)	EC <sub>NI</sub>	NI	27	27		Sweden	2006 (p)	(Adelroth, et al., 2006)
<u>Surface</u>								
Prod./Maint. (NM)	EC <sub>R</sub>	>4	164	13 (2–89)	2 (1.8–6.2)	US	2002(p)	(Cohen, et al., 2002)
Prod./Maint. (NM)	EC <sub>S</sub>	>4	23	23 (15–54)		US	1997(p)	(Stanevich, et al., 1997)
<u>Underground</u>								
Production (NM)	PM <sub>S</sub>	>4	7	154 (68)	142 (1.6)	US	1991	(NIOSH, 1991)
Production (NM)	PM <sub>S</sub>	>4	8	651 (356)	578 (1.7)	US	1991	(NIOSH, 1993)
Production (C)	PM <sub>S</sub>	>4	337	186 <sup>e</sup>		Australia	1990–1994	(Pratt, et al., 1997)
Production (C)	PM <sub>S</sub>	>4	30 (a)	714 (120–410)		US	1991 (p)	(Cantrell, et al., 1991)
Production (C)	PM <sub>S</sub>	>4	24 (a)	635 (110–270)		US	1992 (p)	(Watts, et al., 1992)
Production (C)	PM <sub>S</sub>	>4	181 (a)	620 (20–480)		US	NI	(Ambs, et al.)
Production (C)	PM <sub>S</sub>	>4	≥ 5 (a)	582		US	1992(p)	(Haney, 1992)
Production (C)	PM <sub>S</sub>	>4	16 (a)	1012 (753)	699 (2.7)	US	1992p	(Haney, et al., 1992)
Mining, NS (M)	PM <sub>S</sub>	>4	30 (a)	1600 (1020)		US	1988	(NIOSH, 1992)

Description	Agent	Duration	n	AM (SD)	GM (GSD)	Location	Year	Ref
Mining, NS (M)	PM <sub>S</sub>	>4	14	389 (264)		US	1988	(NIOSH, 1991)
<u>Underground</u>								
Production (NM)	PM <sub>R</sub>	>4	305	2128 (130–2510)	1610	Germany	1999–2003	(Dahmann, et al., 2007)
Production (M/NM)	PM <sub>R</sub>	>4	≥ 5 (a)	847		US	1992(P)	(Haney, 1992)
Production (M)	PM <sub>R</sub>	>4	15	1941 (452–1839)		US	1999	(McDonald, et al., 2002)
Production (C)	PM <sub>R</sub>	>4	2	3437 <sup>e</sup>	3300 (1.3)	Estonia	2002 (p)	(Boffetta, et al., 2002)
Production (C)	PM <sub>R</sub>	>4	20	1379 <sup>e</sup>	1249 (1.4–1.7)	Czech R.	1999–2000	(Scheepers, et al., 2003)
Production (C)	PM <sub>R</sub>	>4	≥ 5 (a)	1629		US	1992(p)	(Haney, 1992)
Production (C)	PM <sub>R</sub>	>4	16	1453 <sup>e</sup>	940 (1.7–2.5)	US	1976–1980	(Wheeler, et al., 1980)
Maintenance (NM)	PM <sub>R</sub>	>4	107	556 (40–830)	364	Germany	1999–2003	(Dahmann, et al., 2007)
Mining, NS (NM)	PM <sub>R</sub>	NI	180	710 (710)		US	1978 (p)	(Gamble, et al., 1978)
Mining, NS (NM)	PM <sub>R</sub>	NI	≥5	3637		US	1976–1977	(Attfield, 1978)
Mining, NS (M)	PM <sub>R</sub>	NI	≥5	940		US	1976–1977	(Attfield, 1978)
Mining, NS (C)	PM <sub>R</sub>	>4	78	1483 (870–1720)		US	1982 (p)	(Reger, et al., 1982)
Mining, NS (C)	PM <sub>R</sub>	>4	60	2000 (1700)		US	1982 (p)	(Ames, et al., 1982)
<u>Surface</u>								
Prod./Maint. (C)	PM <sub>R</sub>	>4	68	881 <sup>e</sup>	651 (1.6–2.3)	Czech R.	1999–2000	(Scheepers, et al., 2003)
<u>Underground</u>								
Production (NM)	CO	1–>4	5	2.0 (0.6)	1.9 (1.4)	US	1991	(NIOSH, 1991)
Mining, NS (NM)	CO	NI	≥ 5 (a)	8.9		US	1976–1977	(Attfield, 1978)
Mining, NS (M)	CO	NI	≥ 5 (a)	6.1		US	1976–1977	(Attfield, 1978)
<u>Underground</u>								
Production (NM)	NO	>4	9	14.7 (2.8)	14.5 (1.2)	US	1991	(NIOSH, 1991)
Production (NM)	NO	>4	7	4.2 (1.7)	3.9 (1.5)	US	1991	(NIOSH, 1991)
Production (NM)	NO	>4	6	4.7 (1.0)	4.6 (1.2)	US	1991	(NIOSH, 1993)
Mining, NS (M)	NO	>4	54 (a)	11.0 (5.7)		US	1988	(NIOSH, 1992)
Mining, NS (M)	NO	>4	25	0.7 (0.6)		US	1988	(NIOSH, 1991; NIOSH, 1992)
<u>Surface</u>								
Prod./Maint. (M)	NO	>4	12	0.3 (0.2)		US	1988	(NIOSH, 1992)

Description	Agent	Duration	n	AM (SD)	GM (GSD)	Location	Year	Ref
<u>Underground</u>								
Production (NM)	NO <sub>2</sub>	>4	9	2.9 (0.5)	2.9 (1.2)	US	1991	(NIOSH, 1991)
Production (NM)	NO <sub>2</sub>	>4	7	0.8 (0.4)	0.7 (1.6)	US	1991	(NIOSH, 1991)
Production (NM)	NO <sub>2</sub>	>4	6	0.7 (0.1)	0.7 (1.1)	US	1991	(NIOSH, 1993)
Production (NM)	NO <sub>2</sub>	NI	183	1.9 (1.6)		US	1978 (p)	(Gamble, et al., 1978)
Production (C)	NO <sub>2</sub>	>4	41	0.2 <sup>e</sup>	0.1 (1.5-2.8)	US	1976-1980	(Wheeler, et al., 1980)
Production (C)	NO <sub>2</sub>	>4	76	0.2 (0.1 -0.1)		US	1982 (p)	(Reger, et al., 1982)
Production (M)	NO <sub>2</sub>	NI	29	0.2		Sweden	2006 (p)	(Adeiroth, et al., 2006)
Production (M)	NO <sub>2</sub>	>4	54 (a)	1.5 (0.9)		US	1988	(NIOSH, 1992)
Production (M)	NO <sub>2</sub>	>4	25	5.5 (3.9)		US	1988	(NIOSH, 1991)
Mining, NS (C)	NO <sub>2</sub>	>4	60	0.2 (0.1)		US	1982 (p)	(Ames, et al., 1982)
<u>Surface</u>								
Prod./Maint. (M)	NO <sub>2</sub>	>4	12	0.04 (0.03)		US	1988	(NIOSH, 1992)

S = submicron, R = respirable, I =inhalable; NI: not indicated; NS, job not specified; NM: nonmetal, M: metal, C: coal; (a): area sample representative of personal exposure; ≥ 5 : at least 5 samples for all jobs combined in the study;

<sup>e</sup>AM estimated from GM and GSD or from range; (p): publication year, sampling year not available

**Table 3**

Occupational exposure measurements of diesel exhaust in the railroad industry: elemental carbon (EC,  $\mu\text{g}/\text{m}^3$ ), submicron and respiratory particulate matter (PM<sub>5</sub> and PM<sub>R</sub>,  $\mu\text{g}/\text{m}^3$ ), and CO, NO and NO<sub>2</sub> (ppm)

Description	Agent	Duration	n	AM (SD)	GM (GSD)	Location	Year	Ref
<u>Train crew</u>								
Driver, assistant, shunter driver	EC <sub>R</sub>	>4	19	20 (18.7)	16 (2.0)	Russia	2002 (p)	(Boffetta, et al., 2002)
Hostler	EC <sub>R/I</sub>	>4	5	4 (1.3)	3 (1.5)	Canada	1999–2000	(Verma, et al., 2003)
Engineer/driver, conductor/trainmen	EC <sub>R/I</sub>	>4	76 (a)	5 (1.1–15.8)	3 (1.5–3.5)	Canada	1999–2000	(Verma, et al., 2003)
Nonoperating crew trailing locomotive	EC <sub>I</sub>	>4	47 (a)	10 (12)	6	Canada	2003	(Seshagiri, 2003)
Engineer's operating console	EC <sub>I</sub>	1→4	49 (a)	6	4 (3)	US	1996–1998	(Liukonen, et al., 2002)
<u>Maintenance</u>								
Rolling equipment	EC <sub>R/I</sub>	>4	48	5 (4.9–8.8)	3 (2.4–2.7)	Canada	1999–2000	(Verma, et al., 2003)
Rolling equipment	EC <sub>R</sub>	>4	64	39	17 (1.9)	UK	2000(p)	(Groves, et al., 2000)
<u>Train crew</u>								
Driver, assistant, shunter driver	PM <sub>R</sub>	>4	17	858 (354)	797 (1.5)	Russia	2002 (p)	(Boffetta, et al., 2002)
Engineer, brakeman	PM <sub>R</sub>	>4	47	111 (p50)		US	1992 (p)	(Schenker, et al., 1992)
Engineer, fire, conductor, brakeman, hostler	PM <sub>R</sub>	NI	206	126		US	1981–1983	(Hammond, et al., 1988)
<u>Maintenance</u>								
Rolling equipment	PM <sub>R</sub>	>4	55	250	203 (1.9)	UK	2000(p)	(Groves, et al., 2000)
Rolling equipment	PM <sub>R</sub>	>4	191	148 (p50)		US	1992 (p)	(Schenker, et al., 1992)
Rolling equipment	PM <sub>R</sub>	>4	120	196		US	1981–1983	(Hammond, et al., 1988)
Non rolling equipment	PM <sub>R</sub>	>4	14	71		US	1981–1983	(Hammond, et al., 1988)
<u>Train crew</u>								
Nonoperating crew trailing locomotive	CO	>4	280 (a)	4.50 (max)		Canada	2003	(Seshagiri, 2003)
Locomotive and caboose	CO	>4	16 (a)	<1		US	1974–1976	(Hobbs, et al., 1977)
<u>Train crew</u>								
Nonoperating crew trailing locomotive	NO	>4	46 (a)	1.13 (0.87)	0.82	Canada	2003	(Seshagiri, 2003)
Locomotive	NO	>4	9 (a)	0.55		Canada	1996	(Verma, et al., 1999)
Locomotive/caboose	NO	>4	16 (a)	0.23		US	1974–1976	(Hobbs, et al., 1977)

Description	Agent	Duration	n	AM (SD)	GM (GSD)	Location	Year	Ref
<u>Maintenance</u>								
Rolling equipment	NO	>4	18	0.26		Canada	1996	(Verma, et al., 1999)
<u>Train crew</u>								
Nonoperating crew trailing locomotive	NO <sub>2</sub>	>4	181 (a)	0.3 (max)		Canada	2003	(Seshagiri, 2003)
Locomotive on board	NO <sub>2</sub>	>4	9 (a)	0.05		Canada	1996	(Verma, et al., 1999)
Locomotive and caboose	NO <sub>2</sub>	>4	16 (a)	0.03		US	1974–1976	(Hobbs, et al., 1977)
<u>Maintenance</u>								
Rolling equipment	NO <sub>2</sub>	>4	18	0.10		Canada	1996	(Verma, et al., 1999)

S = submicron, R = respirable, I = inhalable; NI: not indicated; (a): area sample representative of personal exposure; (p): publication year, sampling year not available;

<sup>‡</sup> Only results from trailing locomotive, no detectable samples in leading locomotive



Table 4

Occupational exposure measurements of diesel exhaust from other off-road vehicles: elemental carbon (EC,  $\mu\text{g}/\text{m}^3$ ), submicron and respiratory particulate matter (PM<sub>S</sub> and PM<sub>R</sub>,  $\mu\text{g}/\text{m}^3$ ), and CO, NO and NO<sub>2</sub> (ppm)

Description	Agent	Duration	n	AM (SD)	GM (GSD)	Location	Year	Ref
<u>Construction</u>								
Tunnel	EC <sub>I</sub>	>4	10	314 <sup>e</sup>	163 (1.5–3.0)	Norway	1996–1999	(Bakke, et al., 2001)
Tunnel	EC <sub>I</sub>	>4	12	132 <sup>e</sup>	87 (2.5)	Sweden	2002–2004	(Lewne, et al., 2007)
Heavy/highway	EC <sub>R</sub>	>4	261	13	8 (2.7)	US	1994–1999	(Woskie, et al., 2002)
Above ground	EC <sub>I</sub>	>4	22	13 <sup>e</sup>	8 (2.8)	Sweden	2002–2004	(Lewne, et al., 2007)
Electric utility installation	EC <sub>I</sub>	>4	120	4		US	1996–1997	(Whittaker, et al., 1999)
<hr/>								
Tunnel	PM <sub>S</sub>	>4	12	121 <sup>e</sup>	119 (1.2)	Sweden	2002–2004	(Lewne, et al., 2007)
Above ground	PM <sub>S</sub>	>4	22	34 <sup>e</sup>	28 (1.9)	Sweden	2002–2004	(Lewne, et al., 2007)
Tunnel	PM <sub>R</sub>	>4	40	1160 (361)		Sweden	1991 (p)	(Ulfvarson, et al., 1991)
Tunnel	PM <sub>R</sub>	>4	336	1700 <sup>e</sup>	1100 (1.4–2.4)	Norway	1996–1999	(Bakke, et al., 2001)
Heavy/highway	PM <sub>R</sub>	>4	260	766	254 (2.5–4.2)	US	1994–1999	(Woskie, et al., 2002)
<hr/>								
Tunnel	CO	>4	78	9 <sup>e</sup>	5.7 (1.5–2.6)	Norway	1996–1999	(Bakke, et al., 2001)
Tunnel	CO	>4	52	5 (3.7)		Sweden	1991 (p)	(Ulfvarson, et al., 1991)
Electric utility installation	CO	>4	27	1 (0.6–0.6)		US	1996–1997	(Whittaker, et al., 1999)
<hr/>								
Tunnel	NO	>4	53	2.6 (1.5)		Sweden	1991 (p)	(Ulfvarson, et al., 1991)
Electric utility installation	NO	>4	27	0.2 (0.2–0.4)		US	1996–1997	(Whittaker, et al., 1999)
<hr/>								
Tunnel	NO <sub>2</sub>	>4	18	0.22 <sup>e</sup>	0.19 (0.58)	Sweden	2002–2004	(Lewne, et al., 2007)
Tunnel	NO <sub>2</sub>	>4	82	0.86 <sup>e</sup>	0.54 (1.5–4.5)	Norway	1996–1999	(Bakke, et al., 2001)
Tunnel	NO <sub>2</sub>	>4	53	0.88 (0.68)		Sweden	1991 (p)	(Ulfvarson, et al., 1991)
Above ground	NO <sub>2</sub>	>4	33	0.02 <sup>e</sup>	0.02 (1.06)	Sweden	2002–2004	(Lewne, et al., 2007)
Electric utility (outside)	NO <sub>2</sub>	>4	24	0.32 (0.2–0.2)		US	1996–1997	(Whittaker, et al., 1999)
<hr/>								
<u>Dock/distribution</u>								
Dockworkers	EC <sub>S</sub>	>4	54	24 (0.4–2.5)	2 (1.3–27.2)	US	1991(p)	(Zaebst, et al., 1991)

Description	Agent	Duration	n	AM (SD)	GM (GSD)	Location	Year	Ref
Dockworkers	EC <sub>S</sub>	>4	≥5	#	7	US	1990	(Zaebst, et al., 1992)
Fork-lift truck	EC <sub>R</sub>	>4	39(a)	36 <sup>e</sup>	27	UK	2004(p)	(Wheatley, et al., 2004)
Dockworkers	EC <sub>R</sub>	>4	27	122	66 (3.3)	UK	2000(p)	(Groves, et al., 2000)
Dockworkers	EC <sub>R</sub>	>4	12	9 <sup>e</sup>	7 (2)	Georgia	1999	(Garshick, et al., 2002)
Dockworkers	EC <sub>I</sub>	>4	5	4 (1.8)	4 (1.5)	Georgia	1992	(NIOSH, 1993)
Fork-lift truck	PM <sub>R</sub>	>4	39(a)	#	106	UK	2004(p)	(Wheatley, et al., 2004)
Dockworkers	PM <sub>R</sub>	>4	11	359 <sup>e</sup>	276 (2.1)	Georgia	1999	(Garshick, et al., 2002)
Dockworkers	PM <sub>R</sub>	>4	25	442	380 (369)	UK	2000(p)	(Groves, et al., 2000)
Dockworkers	NO <sub>2</sub>	>4	≥5	#	0.18	US	1990	(Zaebst, et al., 1992)
<u>Airline personnel</u>								
Baggage and screening	EC <sub>I</sub>	>4	72	11 (5.4)		US	2004	(NIOSH, 2005)
Baggage and screening	CO	>4	61	2.4 <sup>e</sup>		US	2004	(NIOSH, 2005)
Mechanics and refuelers	CO	>4	10	5 (1.5)	4.7 (1.3)	US	1992	(NIOSH, 1994)
Baggage and screening	NO	>4	40	0.13 (0.07)		US	2004	(NIOSH, 2005)
Baggage and screening	NO <sub>2</sub>	>4	40	0.12 (0.07)		US	2004	(NIOSH, 2005)
<u>Loading/unloading ship</u>								
Marine terminal	EC <sub>I</sub>	>4	168	6 (0.9-9.0)		US	2003-2005	(NIOSH, 2006)
Ferry	EC <sub>R</sub>	>4	20	49	37 (2.5)	UK	2000(p)	(Groves, et al., 2000)
Ferry	PM <sub>R</sub>	>4	16	295	198 (2.7)	UK	2000(p)	(Groves, et al., 2000)
Marine terminal	CO	>4	60	2.5		US	2003-2005	(NIOSH, 2006)

S = submicron, R = respirable, I =inhalable; NI: not indicated; (a): area sample representative of personal exposure; ≥ 5 : at least 5 samples for all jobs combined in the study;

<sup>e</sup> AM estimated from GM and GSD or from range; (p): publication year, sampling year not available,

# AM could not be calculated